

Multistar star screens are available in varying model sizes and chassis configurations to meet your unique performance needs:



MULTISTAR XXL-2
(Wheel)



MULTISTAR XL3
(Wheel or Track)



MULTISTAR ONE
(Hook-Lift)

KOMPTECH MULTISTAR / Technical Specifications

Machine Model	MULTISTAR XXL-2	MULTISTAR XL3	MULTISTAR ONE
Power			
Electrical Consumption:	-	-	Up to 25 kW
Power Source / Output Power:	Diesel Engine-Powered Gen Set / 50 kVA	Diesel Engine-Powered Gen Set / 80 kVA	-
Proportion			
Transport Dimensions (LxWxH):	44'11" x 8'5" x 12'10" (13.7 x 2.5 x 3.9 m)	Trailer: 39'1" x 8'2" x 13'1" (11.9 x 2.5 x 4 m) Track: 37'4" x 9'4" x 12'1" (11.3 x 2.8 x 3.6 m)	26'6" x 8'1" x 8'5" (8.2 x 2.5 x 2.6 m)
Working Dimensions (LxWxH):	50'10" x 12'8" x 13'11" (15.5 x 3.9 x 4.2 m)	Trailer: 54'6" x 20'10" x 13'3" (16.6 x 6.4 x 4 m) Track: 48'1" x 21'3" x 12'3" (14.7 x 6.5 x 3.7 m)	52'6" x 8'1" x 13'5" (16 x 2.5 x 4.1 m)
Weight:	~44,000 lbs	Trailer: ~44,000 lbs / Track: ~52,000	~18,400 lbs
Fines Screen Area:	~13.1 yd ² (~11 m ² /hr)	~8.1 yd ² (~6.8 m ² /hr)	-
Overs Screen Area:	6'-13'7" (1.8-4.2 m)	6'-13'7" (1.8-4.2 m)	-
Performance (dependent on material)			
Fraction Output	2-Fraction	3- or 2-Fraction	2-Fraction
Maximum Throughput:	~650 yd ³ /hr (~500 m ³ /hr)	~400 yd ³ /hr (~300 m ³ /hr)	~262 yd ³ /hr (~200 m ³ /hr)

Think for industry expertise, world-class products, parts, service, and support.

Wherever you work.



CONSTRUCTION AND DEMOLITION (C&D)




MUNICIPAL SOLID WASTE (MSW)



ORGANIC WASTE



SINGLE-STREAM RECYCLING



Luke Ellens
DIRECTOR, SALES & SERVICE

Cel. 905 979 2640
lellens@srsequipment.ca

1100 South Service Road,
Suite 419, Stoney Creek,
Ontario, Canada L8E 0C5

srsequipment.ca



Nicolas Morin
VENTES D'ÉQUIPEMENT,
PIÈCES & SERVICE (QUÉBEC)

Cel. 514 838 1075
nmorin@srsequipment.ca

1100 South Service Road,
Suite 419, Stoney Creek,
Ontario, Canada L8E 0C5

srsequipment.ca

